

MODEL	POWER (kW)(HP)		INLET/OUTLET	MAX. FLOW (L/min)	MAX. HEAD (m)	MAX. SUCT (m)	GW (kg)	PACKING DIMENSION (mm)	QUANTITY (set)
XHm/6C	1.1	1.5	3"×3"	1100	11.9	8	28.6	440×258×315	756
XHm/6CR	1.1	1.5	4"×4"	1100	11.9	8	30	440×258×315	756
XHm/6B	1.5	2	3"×3"	1200	14.7	8	29.8	440×258×315	756
XHm/6BR	1.5	2	4"×4"	1200	14.7	8	31	440×258×315	756
XHm/6A	2.2	3	3"×3"	1300	18.5	8	39.6	440×268×315	600
XHm/6AR	2.2	3	4"×4"	1300	18.5	8	40.5	440×268×315	600
XHm/7B	3	4	3"×3"	1300	21.8	8	41	440×268×315	600
XHm/7BR	3	4	4"×4"	1300	21.8	8	42	440×268×315	600
XHm/7AR	4	5.5	4"×4"	2200	18.8	8	87	595×300×395	315

OPERING LIMITS: Fluid temperature up to 60°C; Maximun ambient temperature 40°C.



XHm/6AR

PERFORMANCE CHART AT n=2900 1/min

